


This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

Applicant:	Bayco Products, Inc.	Manufacturer:	VIGEX INTERNATIONAL LTD.
Address:	640 S. Sanden Blvd. Wylie, TX 75098	Address:	#36 4th Innovation Road, Jinding, Zhuhai, Guangdong,
Country:	USA	Country:	China 519085
Contact:	Mr. Jim Conner	Contact:	Tiffany Wen
Phone:	(469) 326 9452	Phone:	(+86)-756-363 0280
FAX:	(214) 938-0481	FAX:	(+86)-15999605209
Email:	jconner@baycoproducts.com	Email:	tiffany.wen@vigex.com
Party Authorized To Apply Mark:	Same as Manufacturer		
Report Issuing Office:	Dallas, TX		

Control Number: 4008947

Authorized by: _____


Thomas J. Patterson, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
545 East Algonquin Road, Arlington Heights, IL 60005
Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672



AUTHORIZATION TO MARK

Standard(s):	<p>Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II & III, Division 1, Hazardous (Classified) Locations (ANSI/UL 913-2011, Seventh Edition, Issued: July 31, 2006, Revised: September 23, 2011)</p> <p>Explosive atmospheres – Part 0: Equipment – General requirements (ANSI/UL 60079-0-2013, Sixth Edition, Issued: July 26, 2013)</p> <p>Explosive Atmospheres – Part 11: Equipment Protection by Intrinsic Safety "i" (ANSI/UL 60079-11-2013, Sixth Edition, Issued: February 15, 2013)</p> <p>Explosive Atmospheres - Part 26: Equipment for Use in Class I, Zone 0 Hazardous (Classified) Locations (ANSI/ISA 60079-26-2011, Issued: July 11, 2011)</p> <p>Intrinsically Safe and Non-Incendive Equipment for Use in Hazardous Locations; General Instruction No. 1: 1993, General Instruction No. 2: 2003 (CAN/CSA-C22.2 No. 157-92, Issued: 1993/10/01 Ed: 1992 (R2006), (R2012))</p> <p>Explosive atmospheres — Part 0: Equipment — General requirements (CAN/CSA-C22.2 No. 60079-0:11, Second Edition, Issued: December 01, 2011)</p> <p>Explosive atmospheres — Part 11: Equipment protection by intrinsic safety "i" (CAN/CSA-C22.2 No. 60079-11:11, First Edition, Issued: December 01, 2011)</p> <p>Enclosures for Use in Class II Groups E, F, and G Hazardous Locations (CAN/CSA C22.2 No. 25-1966, General Instruction No. 1, R2009)</p>
Product:	<p>XPP-5454/ XPP 5454 GC Intrinsically Safe LED Flashlight Headlamp</p> <p>For use in Hazardous (Classified) Locations: Class I, Division 1, Groups A-D, T3 Class II, Division 1, Groups E-G, Class III, T135C Class I, Zone 0, AEx ia IIC T3 Ga Class I, Zone 0, Ex ia IIC T3 Ga Ambient Temperature Range: -20°C to +40°C IP54</p>
Brand Name:	Nightstick
Models:	XPP-5454; XPP 5454 GC