

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E467756  
**Report Reference** E467756-20200731  
**Issue Date** 2020-AUGUST-06

**Issued to:** BAYCO PRODUCTS INC  
640 SANDEN BLVD  
WYLIE TX 75098-4922

**This certificate confirms that  
representative samples of**

FLASHLIGHTS AND LANTERNS FOR USE IN  
HAZARDOUS LOCATIONS; FLASHLIGHTS AND  
LANTERNS FOR USE IN ZONE CLASSIFIED  
HAZARDOUS LOCATIONS

See Addendum Page

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:**

See Addendum for additional Standards

**Additional Information:**

See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E467756  
**Report Reference** E467756-20200731  
**Issue Date** 2020-AUGUST-06

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model Nightstick XPR-5554, followed by G or GC; intrinsically safe headlight for use in Class I, Division 1, Groups A, B, C and D; Class II, Division 1, Groups E, F and G; and Class III Hazardous Locations when used with rechargeable Li-ion battery pack Part No. Nightstick 5554-BATT.

Model Nightstick XPR-5554, followed by G or GC; intrinsically safe headlight for use in Hazardous Locations, Class I, Zone 0, AEx ia IIC T4 Ga, when used with rechargeable Li-ion battery pack Part No. Nightstick 5554-BATT.

Model Nightstick XPR-5554, followed by G or GC; intrinsically safe headlight for use in Hazardous Locations, Ex ia IIC T4 Ga, when used with rechargeable Li-ion battery pack Part No. Nightstick 5554-BATT.

**Additional Standards for Safety:**


UL 913, Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II, and III, Division 1, Hazardous (Classified) Locations

UL 60079-0, Explosive Atmospheres - Part 0: Equipment - General Requirements

UL 60079-11 and CAN/CSA C22.2 NO. 60079-11:14, Explosive Atmospheres - Part 11: Equipment Protection by Intrinsic Safety 'i'

CAN/CSA C22.2 No. 157-92, Intrinsically Safe and Non-Incendive Equipment for use in Hazardous Locations

CSA C22.2 No. 60079-0, Electrical Apparatus for Explosive Gas Atmospheres - Part 0: General Requirements



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

