

QPS Evaluation Services Inc

Testing, Certification and Field Evaluation Body Accredited in Canada, the USA, and Internationally

Page 1 of 2

File LR3081

CERTIFICATE OF COMPLIANCE

(ISO TYPE 3 CERTIFICATION SYSTEM)

Issued to i.safe MOBILE GmbH

Address i Park Tauberfranken 10

97922 Lauda-Koenigshofen

Germany

Project Number LR3081-4

Product Intrinsically Safe, robust inspection system for leakage detection

Model Number IS-VS1A.1

Electrical Ratings Powered by connecting to QPS certified (LR 3081-2) intrinsically safe 5G

smartphone IS540.1 via ISM-Interface.

Markings Class I, Division 1, Group ABCD, T4

Class II, Division 1, Group EFG, 135°C

Class III

Intrinsically Safe -20°C ≤ Tamb ≤ 55°C

IP54

Applicable Standards CSA C22.2 No. 60079-0:15 4th ed UL 60079-0 7th ed. UL 60079-11 6th ed.

CSA C22.2 No. 60079-11:14 2nd ed.

Factory/Manufacturing Location i Park Tauberfranken 10

97922 Lauda-Koenigshofen

Germany

Conditions of Certification See Annex A

Statement of Compliance: The product(s)/equipment identified in this Certificate and described in the Certification Report covered under the above referenced project number have been investigated and found to be in compliance with the relevant requirements of the above referenced standard(s). As such, they are eligible to bear the QPS Certification Mark shown below, in accordance with the provisions of QPS's Service Agreement.

IMPORTANT NOTE: In order to maintain the integrity of the QPS Mark(s), certification will be revoked if:

- (1) Compliance to the above-mentioned Standard(s), or those identified in future QPS Standard Update Notice SUN (QSD 55) is not maintained, or,
- (2) If the product/equipment is modified after certification is granted without prior written consent by QPS



Issued By: Rob Kohuch, P.Eng.

Signature: Rob Kohul-Date: May 7,2024





Rev 01



QPS Evaluation Services Inc

Testing, Certification and Field Evaluation Body Accredited in Canada, the USA, and Internationally

Page 2 of 2

File LR3081

Annex A: Conditions of Certification:

- 1. The 16-pin connector of IS-VS1A.1 shall only be installed or removed from the ISM interface outside of potentially explosive areas.
- 2. The device shall be protected from excessive exposure to UV light emissions and aggressive acids or alkalis.
- 3. The device shall be protected from high electrostatic charge environments and processes.
- 4. The device is intended to be used with the QPS certified (LR 3081-2) intrinsically safe 5G smartphone IS540.1 and carried over during use in the hazardous area.
- 5. Accessories such as sensors, waveguide and waveguide lock shall be always earthed when used inside hazardous location as per operating manual.



